

CLEANING AND MAINTENANCE OF POLYASPARTIC FLOORING SYSTEMS

Polyaspartic Flooring Systems are designed to provide an Impervious and Highly Abrasion Resistant finish, along with many other benefits, which make it ideally suited to a wide range of Commercial and Industrial Environments.

Their durability and composition allows them to be easily cleaned, when a suitable cleaning regime is used.

The cleaning and maintenance of a **Polyaspartic Flooring System** is considered vital and integral in helping it to achieve and maintain its Maximum Performance and Longevity.

PROTECTION OF NEWLY APPLIED FLOORS

If a **Polyaspartic Flooring System** is installed at an early stage during new or refurbishment projects, the floor may be subjected to various types of usage, which are vastly different from those expected during its normal service.

THESE INCLUDE:

- Heavy lifting equipment
- Movement of heavy machinery
- Spillage of paints, oils, chemicals, etc.

IT IS IMPORTANT TO CONSIDER THE FOLLOWING CAREFULLY:

- Contacting **Clifford Flooring Pty. Ltd.** if you are unsure as to how it is best to protect your New Flooring System from damage during completion of the project works or shutdown periods.
- The installation of temporary covers such as plywood sheets with heavy-duty masking tape at the joins, if the **new Flooring System** will be subject to other trades or traffic before it has fully cured.
- The curing time of the New **Polyaspartic Flooring System** will be dependent on the temperature.
- Do not cover the **New Flooring System** with plastic or with any other impervious coverings, as this will create condensation, which will cause the **New Flooring System** to bloom.
- The avoidance of early heavy usage, particularly with hard-wheeled vehicles, will minimise the risk of damage and or dirt being embedded, before it reaches full hardness.

MAINTENANCE & REPAIR

Good Standards of Hygiene can only be maintained if the integrity of your **Polyaspartic Flooring System** is complete.

It is important to consult **Clifford Flooring Pty Ltd** or a specialist cleaning product manufacturer, before cleaning your floor. Thereby, a cleaning plan that best suits your particular environment can be arranged.

It is always recommended that pH neutral, non-foaming and nonabrasive products are used.

Even the most assiduously cleaned **Polyaspartic Flooring System** may suffer damage to its integrity by unforeseen incidents in the workplace. This can result in the consequential risk of bacteriological build-up in cracks etc. If this situation arises, the damaged **Polyaspartic Floor System** should be repaired without delay, by contacting **Clifford Flooring Pty. Ltd.** immediately.